


NEW HOUSE FOR

# GOLDSILVERISLAND, LLC

622 COVINGTON ROAD, LOS ALTOS, CA. 94024



A.P.N.: 189 - 45 - 035 ZONING: R1-10 LOT SIZE: 14,199 S.F. 1,201 S.F. (TO BE REMOVED) EXISTING HOUSE: 2,299 S.F. FIRST FLOOR: 1,372 S.F. SECOND FLOOR: 3,670 S.F. TOTAL HOUSE: GARAGE: 460 S.F. 4,131 S.F. TOTAL BUILDING: F.A.R. ALLOWED: 14,199 - 11,000 = 3199 3,850 + 319.9 = 4,169.9 S.F. 4,131 S.F. PROPOSED: LANDSCAPE ARCHITECT Mara Young 650-327-2644 marayoung@gmail.com SOILS ENGINEER CAPEX Engineering Gary Hsu, PE POB 14198 Fremont, CA 94539 510-668-1815 capexinc888@gmail.com

ARBORIST

Kevin Kielty

POB 6187

KIELTY ARBORIST SERVICES

650-515-9783 kkarbor0476@yahoo.com

San Mateo, CA 94403

SHEET INDEX A-1 SITE PLAN A-1.2 TREE PROTECTION PLAN A-2 FIRST FLOOR PLAN A-3 SECOND FLOOR PLAN A-4 ELEVATIONS A-5 ELEVATION, SECTIONS A-6 SECTION, ROOF PLAN A-7 AREA CALCS C-1 GRADING & DRAINAGE C-2 NOTES & DETAILS C-3 EROSION CONTROL PLAN C-4 DETAILS L-O LANDSCAPE COVER SHEET L-1 LANDSCAPE PLAN L-2 IRRIGATION PLAN L-3 HYDROZONE DIAGRAM OWNER Goldsilverisland Properties, LLC Ying-Min Li 1525 McCarthy Blvd, Suite 1000 Milpitas, CA 95035 yingminli@hotmail.com 408-896-3369 ARCHITECT HOMETEC Architecture, Inc.

Richard A. Hartman, AIA

408-995-0496 hometecarch@gmail.com

408-262-1899 rwengineering@gmail.com

619 N 1st Street

CIVIL ENGINEER

Robert Wang

RW ENGINEERING

505 Altamont Drive


Milpitas, CA 95036

San Jose, CA 95112

ZONING COMPLIANCE Existing Proposed Allowed/Required LOT COVERAGE: 2,758 square feet 4,259 square feet 1,662 square feet Land area covered by all structures that (\_11.7\_%) 19.4%) are over 6 feet in height FLOOR AREA: 4,131 square feet 1,567 square feet 4,169 square feet Measured to the outside surfaces of 29\_%) (\_11\_%) (<u>29.3</u>%) SETBACKS: 36 feet 25 feet 25 feet 75\_feet 30.5 feet Rear (TOP OF BANK) 25 feet 10.25 feet/20.5 feet \_\_\_\_\_10\_\_\_feet/<u>17.5</u>feet \_\_<u>16\_\_feet/\_\_\_feet</u> Right side (1st/2nd) 22.2 feet/26.8 feet 16.6 feet/16.6 feet Left side (1st/2nd) 26.5 feet \_\_\_\_\_feet HEIGHT: 16 feet SQUARE FOOTAGE BREAKDOWN Existing Total Proposed Change in HABITABLE LIVING AREA: 3,671 square feet 1,201 square feet 2,491 square feet Includes habitable basement areas NON- HABITABLE AREA: 460 square feet Does not include covered porches or open 366 square feet 94 square feet LOT CALCUATIONS 14,199 square feet NET LOT AREA: FRONT YARD HARDSCAPE AREA: 490 square feet ( 24%) Hardscape area in the front yard setback shall not exceed 50% **2,719** sq ft Total hardscape area (existing and proposed): **4,055** sq ft Existing softscape (undisturbed) area: LANDSCAPING BREAKDOWN: New softscape area: 7,425 sq ft

Sum of all three should equal the site's net lot area

AND **FRISL/** GOLD Date 7 - 18 - 17 1/4" = 1'-*0*" RAH Drawn 17-016 Sheet **T-1** 



Kielty Arborist Services LLC Certified Arborist WE#0476A P.O. Box 6187 San Mateo, CA 94403 650-515-9783

June 14, 2017

#### Goldsilverisland Homes, LLC

Attn: Mr. Ying-Min Li 43575 Mission Blvd, suite 359 Fremont, CA, 94539

Site: 622 Covington, Los Altos, CA

Dear Mr. Li,

As requested on Thursday, June 8, 2017, I visited the above site to inspect and comment on the trees. A new home and landscape is planned for this site and a survey of the trees will be required. A tree protection plan will be included as required by the city of Los Altos.

#### Method:

All inspections were made from the ground; the tree was not climbed for this inspection. Each tree in was located on a map provided by you. The trees were then measured for diameter at 54 inches above ground level (DBH or diameter at breast height). The trees were given a condition rating for form and vitality. The trees' condition rating is based on 50 percent vitality and 50 percent form, using the following scale.

- 1 29 Very Poor 30 - 49 Poor
- 50 69 Fair
- 70 89 Good
- 90 100 Excellent

The height of the tree was measured using a Nikon Forestry 550 Hypsometer. The spread was paced off. Comments and recommendations for future maintenance are provided.

622 Covington/6/14/17

**Survey:** 

**DBH CON HT/SP Comments** Tree# Species

20 40 50/35 Poor vigor, poor form, nearly dead. 15 Coast live oak (Quercus agrifolia)

6.8 40 10/20 Poor-fair vigor, poor form, verticilium wilt. 16 Japanese maple (Acer palmatum)

# \*indicates neighbor's tree

The trees on site are a mix of native oaks and several species of imported trees. The trees are in poor-fair condition with the large protected tree being located on the perimeter. Trees on the perimeter are ideally located for construction. The small ornamental trees will be removed to facilitate the construction.

## **Tree Protection Plan:**

Tree protection zones should be established and maintained throughout the entire length of the project. Fencing for the protection zones should be 6 foot tall metal chain link type supported by metal poles pounded into the ground. The support poles should be spaced no more than 10 feet apart on center. The location for the protection fencing should be as close to the dripline as possible still allowing room for construction to safely continue. Signs should be placed on fencing signifying "Tree Protection Zone - Keep Out". No materials or equipment should be stored or cleaned inside the tree protection zones. Areas outside the fencing but still beneath the dripline of protected trees, where foot traffic is expected to be heavy, should be mulched with 4 to 6 inches of chipper chips.

Trenching for irrigation, electrical, drainage or any other reason should be hand dug when beneath the driplines of protected trees. Hand digging and carefully laying pipes below or beside protected roots will dramatically reduce root loss of desired trees thus reducing trauma to the entire tree. Trenches should be backfilled as soon as possible with native material and compacted to near its original level. Trenches that must be left exposed for a period of time should also be covered with layers of burlap or straw wattle and kept moist. Plywood over the top of the trench will also help protect exposed roots below.

Normal irrigation should be maintained throughout the entire length of the project. The imported trees on this site will require irrigation during the warm season months. Some irrigation may be required during the winter months depending on the seasonal rainfall. During the summer months the trees on this site should receive heavy flood type irrigation 2 times a month. During the fall and winter 1 time a month should suffice. Mulching the root zone of protected trees will help the soil retain moisture, thus reducing water consumption.

622 Covington/6/14/17

Survey: **DBH CON HT/SP Comments** Tree# Species 24.1 65 45/40 Good vigor, fair form, heavy lateral limbs. 1 Deodar cedar (Cedrus deodara) 30est 60 55/40 Fair vigor, fair form, 6 feet from property 2\* Redwood (Sequoia sempervirens) 45 10/15 Poor-fair vigor, poor form, codominant at Japanese maple 2 feet. (Acer palmatum) 50 8/10 Fair vigor, poor-fair form, squatty. Japanese maple (Acer palmatum) 8.3 50 20/15 Good vigor, fair form, multi leader at 2 feet, Japanese maple (Acer palmatum) poor crotch. 6\* Coast live oak 28est 65 45/45 Good vigor, fair form, multi leader, 5 feet from property line. (Quercus agrifolia) 8.2 40 10/15 Poor vigor, poor form, decay at base. 7 Japanese maple (Acer palmatum) 8 Valley oak 65 50/45 Fair vigor, poor-fair form, codominant at (Quercus lobata) 19.9 40 20/30 Fair vigor, poor form, suppressed by #8. 9 Coast live oak (Quercus agrifolia) 10 Redwood 12.0 50 35/20 Good vigor, poor-fair form, suppressed.

(2)

14.1-18.6 55 40/20 Good vigor, fair form, suppressed. 11 Redwood (Sequoia sempervirens)

Valley oak 79.2 @base 65 55/60 Good vigor, fair form, multi leader (Quercus lobata) 9.9 60 35/25 Good vigor, fair form, suppressed. 13 Redwood

10.2 60 40/25 Good vigor, fair form, suppressed. 14 Redwood (Sequoia sempervirens)

622 Covington/6/14/17

(Sequoia sempervirens)


(Sequoia sempervirens)

Tree trimming to facilitate the construction is not planned for the site. If ornamental trimming is to be carried out the work will be done by a licensed tree care provider. All trimming will be within ANSI standards and Best Management Practices and will be inspected by the site arborist.

The information included in this report is believed to be true and based on sound arboricultural principles and practices.

Sincerely,

Kevin R. Kielty Certified Arborist WE#0476A





GOLDSILVERISLAND
622 COVINGTON ROAD, LOS ALTO

RAH

17-016

A-1.2





PLANNING
8-17-17

ICHARD A. HARTMAN
A.I.A.

408/995-0496

HometecArch@Gmail.com

HOME' ARCHITECTU

CA. 94024

GOLDSILVERISLAND
S22 COVINGTON ROAD, LOS ALTOS

Date 7 - 18 - 17


Scale 1/4" = 1'-0"


Drawn RAH


Job 17-016

**A-3** 

SECOND FLOOR PLAN








**REVISIONS** 


GOLDSILVERISLAND
622 COVINGTON ROAD, LOS ALTOS


Date 7 - 18 - 17 Scale 1/4" = 1'-0"

RAH 17-016

Sheet **A-6** 







#### **GRADING NOTES:**

NOT TO SCALE

- 1. ALL MATERIAL AND WORKMANSHIP SHALL CONFORM TO GENERAL AND SPECIFIC PROVISIONS, STANDARD DRAWINGS, AND REQUIREMENT OF THE CITY OF LOS ALTOS.
- 2. THE OWNER AND THE ENGINEER OF WORK WILL NOT BE RESPONSIBLE FOR ENFORCING SAFETY MEASURES AND REGULATIONS. THE CONTRACTOR MUST DESIGN, CONSTRUCT, INSTALL, AND MAINTAIN ALL SAFETY DEVICES, INCLUDING SHORING, AND SHALL BE SOLELY RESPONSIBLE FOR CONFORMING TO ALL LOCAL, STATE, AND FEDERAL SAFETY AND HEALTH STANDARDS, LAW AND REGULATIONS.
- 3. PRIOR TO START OF CONSTRUCTION, CONTRACTOR MUST VERIFY ALL JOINT/CROSSING LOCATIONS, ELEVATIONS, CURB, GUTTER, SIDEWALK, FLOW LINES, PAVEMENT, STREETS, AND ALL GRADE JOINTS. IF DISCREPANCY IS FOUND, THE CONTRACTOR MUST IMMEDIATELY NOTIFY THE ENGINEER AND NOT PROCEED WITH ANY CONSTRUCTION UNTIL VERIFICATION AND REVISION (IF NECESSARY) IS COMPLETED BY THE SAID ENGINEER.
- 4. CONTRACTOR TO EXPOSE EXISTING SEWERS AND CHECK INVERTS BEFORE CONSTRUCTING NEW SEWERS. NOTIFY THE ENGINEER 24 HOURS
- 5. THE EXISTENCE AND LOCATION OF ALL UNDERGROUND UTILITIES/STRUCTURES SHOWN HEREON WERE OBTAINED FROM INFORMATION FURNISHED BY OTHERS. THE ENGINEER ASSUMES NO RESPONSÍBILITY FOR THE COMPLETENESS AND ACCURACY OF SAID INFORMATION. THE CONTRACTOR MUST ASCERTAIN THE TRUE VERTICAL AND HORIZONTAL LOCATION AND SIZE OF THOSE TO BE USED AND SHALL BE RESPONSIBLE FOR DAMAGE TO ANY PUBLIC OR PRIVATE UTILITIES SHOWN OR NOT SHOWN HEREON.
- 6. THE SOIL REPORTS PREPARED FOR THE PROJECT IS A PART OF THIS PLAN. THE MOST STRINGENT REQUIREMENTS BY SOIL ENGINEER OR GOVERNING AGENCIES SHALL PREVAIL.
- 7. GRADING SHALL BE DONE IN ACCORDANCE WITH THE REQUIREMENTS AND RECOMMENDATIONS CONTAINED IN THE SOIL REPORT FOR THIS SITE TOGETHER WITH ANY SUPPLEMENTS THERETO. ALL GRADING WORK SHALL BE DONE UNDER THE OBSERVATION OF THE SOILS ENGINEER. THE SOIL ENGINEER SHALL BE NOTIFIED 48 HOURS BEFORE THE START OF ANY GRADING.
- 8. PRIOR TO START OF ANY WORK, CONTRACTOR MUST REVIEW THE PLANS FOR DESIGN INCONSISTENCIES AND TYPOS SUCH AS ELEVATIONS, CURB HEIGHT, DIMÉNSIONS, SLOPES, ETC. IF INCONSISTENCIES OR OBVIOUS TYPOS ARE FOUND, THE CONTRACTOR MUST IMMEDIATELY NOTIFY THE ENGINEER OF WORK FOR VERIFICATION BEFORE PROCEEDING WITH ANY WORK
- 9. THE LANDSCAPE FINISHED GRADES WITHIN FIVE FEET (TEN FEET IF BUILDING SETBACK ALLOWS) OF THE BUILDING OR STRUCTURE SHALL SLOPE AT A 2% MINIMUM FROM THE FOUNDATION. ALL EXTERIOR HARD SURFACING AREAS (INCLUDING TERRACES) SHALL BE INSTALLED WITH A 2% MINIMUM GRADIENT, AND SHALL DRAIN AWAY FROM THE BUILDING. FINISHED GRADE DRAINAGE SWALES SHALL HAVE A MINIMUM SLOPE OF 1%. MAXIMUM GRADED SLOPE IS 3:1 (3 HORIZONTAL TO 1 VERTICAL). SPOT ELEVATIONS SHOWN ON THE PLAN SHALL DICTATE ACTUAL GRADES. SURFACE SLOPE GRADES NOTED ON THE PLAN ARE APPROXIMATE.
- 10. FOR ALL UTILITY NOTES MARKED "VERIFY", CONTRACTOR SHALL VERIFY LOCATION, SIZE, MATERIAL, ETC, OF EXISTING UTILITIES, SUCH AS WATER, GAS SEWER, ETC., PRIOR TO STARTING CONSTRUCTION.
- 11. SEE ARCHITECTURAL SITE PLAN AND LANDSCAPE PLAN FOR SITE INFORMATION AND NOTES NOT SHOWN HEREIN.

#### GENERAL EROSION AND SEDIMENT CONTROL NOTES:

- 1. THIS PLAN IS INTENDED TO BE USED FOR INTERIM EROSION AND SEDIMENT CONTROL ONLY AND IS NOT TO BE USED FOR FINAL ELEVATIONS OR PERMANENT IMPROVEMENTS.
- 2. OWNER/ CONTRACTOR SHALL BE RESPONSIBLE FOR MONITORING EROSION AND SEDIMENT CONTROL MEASURES PRIOR, DURING, AND AFTER STORM EVENTS.
- 3. REASONABLE CARE SHALL BE TAKEN WHEN HAULING ANY EARTH, SAND, GRAVEL, STONE, DEBRIS, PAPER OR ANY OTHER SUBSTANCE OVER ANY PUBLIC STREET, ALLEY OR OTHER PUBLIC PLACE. SHOULD ANY BLOW, SPILL, OR TRACK OVER AND UPON SAID PUBLIC OR ADJACENT PRIVATE PROPERTY, IMMEDIATE REMEDY SHALL OCCUR.
- 4. SANITARY FACILITIES SHALL BE MAINTAINED ON THE SITE.
- 5. DURING THE RAINY SEASON, ALL PAVED AREAS SHALL BE KEPT CLEAR OF EARTH MATERIAL AND DEBRIS. THE SITE SHALL BE MAINTAINED SO AS TO MINIMIZE SEDIMENT LADEN RUNOFF TO ANY STORM DRAINAGE SYSTEM, INCLUDING EXISTING DRAINAGE SWALES AND WATER COURSES.
- 6. CONSTRUCTION OPERATIONS SHALL BE CARRIED OUT IN SUCH A MANNER THAT EROSION AND WATER POLLUTION WILL BE MINIMIZED. STATE AND LOCAL LAWS CONCERNING POLLUTION ABATEMENT SHALL BE COMPLIED WITH.
- 7. CONTRACTOR SHALL PROVIDE DUST CONTROL AS REQUIRED BY THE APPROPRIATE FEDERAL, STATE, AND LOCAL AGENCY REQUIREMENTS.

## EROSION AND SEDIMNET CONTROL MEASURES

- 1. THE FACILITIES SHOWN ON THIS PLAN ARE DESIGNED TO CONTROL EROSION AND SEDIMENT DURING THE RAINY SEASON. OCTOBER 15 TO APRIL 15. FACILITIES ARE TO BE OPERABLE PRIOR TO OCTOBER 1 OF ANY YEAR. GRADING OPERATIONS DURING THE RAINY SEASON WHICH LEAVE DENUDED SLOPES SHALL BE PROTECTED WITH EROSION CONTROL MEASURES IMMEDIATELY FOLLOWING GRADING ON THE
- 2. THIS PLAN COVERS ONLY THE FIRST WINTER FOLLOWING GRADING WITH ASSUMED SITE CONDITIONS AS SHOWN ON THE EROSION CONTROL PLAN. PRIOR TO SEPTEMBER 15. THE COMPLETION OF SITE IMPROVEMENT SHALL BE EVALUATED AND REVISIONS MADE TO THIS PLAN AS NECESSARY WITH THE APPROVAL OF THE CITY ENGINEER. PLANS ARE TO BE RESUBMITTED FOR CITY APPROVAL PRIOR TO SEPTEMBER 1 OF EACH SUBSEQUENT YEAR UNTIL SITE IMPROVEMENTS ARE ACCEPTED BY THE CITY AND COUNTY.
- 3. CONSTRUCTION ENTRANCES SHALL BE INSTALLED PRIOR TO COMMENCEMENT OF GRADING. ALL CONSTRUCTION TRAFFIC ENTERING ONTO THE PAVED ROADS MUST CROSS THE STABILIZED CONSTRUCTION ENTRANCE WAYS. (ALSO INCLUDE THIS NOTE ON GRADING PLANS.)
- 4. CONTRACTOR SHALL MAINTAIN STABILIZED ENTRANCE AT EACH VEHICLE ACCESS POINT TO EXISTING PAVED STREETS. ANY MUD OR DEBRIS TRACKED ONTO PUBLIC STREETS SHALL BE REMOVED DAILY AND AS REQUIRED BY THE CITY AND COUNTY.
- 5. IF HYDROSEFDING IS NOT USED OR IS NOT EFFECTIVE BY 10/10. THEN OTHER IMMEDIATE METHODS SHALL BE IMPLEMENTED. SUCH AS EROSION CONTROL BLANKETS, OR A THREE-STEP APPLICATION OF 1) SEED, MULCH, FERTILIZER 2) BLOWN STRAW 3) TACKIFIER AND MULCH.
- 6. INLET PROTECTION SHALL BE INSTALLED AT OPEN INLETS TO PREVENT SEDIMENT FROM ENTERING THE STORM DRAIN SYSTEM. INLETS NOT USED IN CONJUNCTION WITH EROSION CONTROL ARE TO BE BLOCKED TO PREVENT ENTRY OF SEDIMENT.
- 7. LOTS WITH HOUSES UNDER CONSTRUCTION WILL NOT BE HYDROSEEDED. EROSION PROTECTION FOR EACH LOT WITH A HOUSE UNDER CONSTRUCTION SHALL CONFORM TO THE TYPICAL LOT EROSION CONTROL DETAIL SHOWN ON THIS SHEET.
- 8. THIS EROSION AND SEDIMENT CONTROL PLAN MAY NOT COVER ALL THE SITUATIONS THAT MAY ARISE DURING CONSTRUCTION DUE TO UNANTICIPATED FIELD CONDITIONS. VARIATIONS AND ADDITIONS MAY BE MADE TO THIS PLAN IN THE FIELD. NOTIFY THE CITY REPRESENTATIVE OF ANY FIELD CHANGES.

## MAINTENANCE NOTES

- 1. MAINTENANCE IS TO BE PERFORMED AS FOLLOWS:
- A. REPAIR DAMAGES CAUSED BY SOIL EROSION OR CONSTRUCTION AT THE END OF EACH WORKING DAY. B. SWALES SHALL BE INSPECTED PERIODICALLY AND MAINTAINED AS NEEDED.
- C. SEDIMENT TRAPS, BERMS, AND SWALES ARE TO BE INSPECTED AFTER EACH STORM AND REPAIRS MADE AS NEEDED. D. SEDIMENT SHALL BE REMOVED AND SEDIMENT TRAP RESTORED TO ITS ORIGINAL DIMENSIONS WHEN SEDIMENT HAS ACCUMULATED TO A
- DEPTH OF 1 FOOT. E. SEDIMENT REMOVED FROM TRAP SHALL BE DEPOSITED IN A SUITABLE AREA AND IN SUCH A MANNER THAT IT WILL NOT ERODE.
- F. RILLS AND GULLIES MUST BE REPAIRED.
- 2. ROCK BAG INLET PROTECTION SHALL BE CLEANED OUT WHENEVER SEDIMENT DEPTH IS ONE HALF THE HEIGHT OF ONE ROCK BAG.

## **HYDROSEEDING:**

- 1. ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS, CALTRANS STANDARD SPECIFICATIONS, AND UNDER THE DIRECTION OF THE SOIL ENGINEER IN THE FIELD.
- 2. ALL AREAS SPECIFIED FOR HYDROSEEDING SHALL BE NOZZLE PLANTED WITH STABILIZATION MATERIAL CONSISTING OF FIBER, SEED, FERTILIZER AND WATER, MIXED AND APPLIED IN THE FOLLOWING PROPORTIONS AVAILABLE FROM PACIFIC COAST SEED, LIVERMORE (925) 373-4417:

FIBER (HYDROSTRAW AND TACK MULCH) 2500 LBS/ACRE COLOR (GREEN TO GOLD) 55 LBS/ACRE FERTILIZER (16-20-0) 350 LBS/ACRE M-BINDER 125 LB/ACRE WATER, AS REQUIRED FOR APPLICATION

/ ENGINEERING, INC.
ENGINEERS LAND SURVEYORS
TAMONT DRIVE, MILPITAS, CA 9503:
7262-1899 (FAX) (408) 824-55
rwengineering@gmail.com

CIVIL E ALT, (408)



DATE: 7/7/17


A O

Y L S  $\Box$ 

20) - E E

DATE: 7/7/17 SCALE: AS NOTED DESIGNED BY: RW

DRAWN BY: RW SHEET



DATE: 7/4/17

 $\leq$  O

DATE: 7/4/17 SCALE: AS NOTED DESIGNED BY: RW

**C-3** 







DATE: 7/4/17


AND


DATE: 7/4/17 SCALE: AS NOTED DESIGNED BY: RW DRAWN BY: RW

SHEET











EC-2





TYPICAL EROSION AND

SEDIMENT CONTROL AT

CONSTRUCTION SITE

EC-1

## ZONING COMPLIANCE

	Existing	Proposed	Allowed/Required
LOT COVERAGE:  Land area covered by all structures that are over 6 feet in height			
FLOOR AREA:  Measured to the outside surfaces of exterior walls		4,152 square feet (29.2%)	4.169.9 square feet (29.3%)
SETBACKS: Front Rear (TOP OF BANK) Right side (1st/2nd) Left side (1st/2nd)	36 feet	25 feet 30.5 feet 10.25 feet/8.75 eet 22.2 feet/26.8 feet	
HEIGHT:	16feet	_26.5 feet	feet

## SQUARE FOOTAGE BREAKDOWN

	Existing	Change in	Total Proposed
HABITABLE LIVING AREA: Includes habitable basement areas	square feet	2,491 square feet	
NON- HABITABLE AREA:  Does not include covered porches or open structures	366 square feet	94square feet	460_square feet

## LOT CALCUATIONS

NET LOT AREA:		14,199 square feet	
FRONT YARD HARDSCAPE ARI Hardscape area in the front yard setback s		490square feet (	<u>24</u> %)
LANDSCAPING BREAKDOWN:	Existing softscape (un New softscape area:	(existing and proposed): adisturbed) area: qual the site's net lot area	2,719 sq ft 4,055 sq ft 7,425 sq ft

OFFICE OF COUNTY ASSESSOR —— SANTA CLARA COUNTY, CALIFORNIA 43) 42 TRACT No. 372 LOS ALTOS RANCHO 13-M-29

PROJECT DESCRIPTION: LANDSCAPE PLANS FOR NEW HOME

R1-10 R-3, U ZONING

**PROPERTY OWNER:** GOLDSILVERISLAND

1525 McCARTHY BLVD, SUITE 1000

MILPITAS, CA 95035-7451 phone (408) 896-3369

email: yingminli@hotmail.com

**622 COVINGTON ROAD** PROJECT SITE: LOS ALTOS, CA 94024

**DESIGN CONTACT:** MARA YOUNG LANDSCAPE ARCHITECT CA. LANDSCAPE ARCHITECT #3754

836 18th AVENUE, MENLO PARK, CA 94025

(650) 327-2644

marayoung@gmail.com

# TABLE OF CONTENTS

L-0 COVER SHEET

LANDSCAPE PLAN

**IRRIGATION PLAN** 

HYDROZONE DIAGRAM AND WATER USE INFO

# PROJECT INFORMATION

APN: 189-45-035 **SITE AREA:** 14,199 S.F.


842 S.F. MORTARED STONE ON CONC. 1102 S.F. PAVERS ON SAND **DECOMPOSED GRANITE PATHS** 775 S.F.


TOTAL HARDSCAPE 2719 S.F.

SOFTSCAPE 7425 S.F.

> I HAVE COMPLIED WITH THE CRITERIA OF THE CALIFORNIA WATER EFFICIENT LANDSCAPE ORDINANCE AND APPLIED THEM FOR THE EFFICIENT USE OF WATER IN THE LANDSCAPE AND IRRIGATION DESIGN PLAN

> I AGREE TO COMPLY WITH THE REQUIREMENTS OF THE MATER EFFICIENT LANDSCAPE ORDINANCE AND SUBMIT A COMPLETE LANDSCAPE DOCUMENTATION PACKAGE






ANDS(COVE


NEW HOME FOR:
GOLDSILVERISLAND
622 COVINGTON WAY
LOS ALTOS, CA 9402

APN# 189-45-035
DRAWN
MY
CHECKED
MY
DATE
6/14/17
SCALE
XXX
JOB NO.
xxx
SHEET

**L-0** 









#4 CHOISYA TERNATA- MOCK ORANGE MATURE SIZE: 6' HIGH x 6' WIDE



#5 OLEA 'LITTLE OLLIE'- DWARF OLIVE MATURE SIZE: 6'-8' HIGH x 6'-8' WIDE



#6 COTINUS COGGYGRIA 'ROYAL PURPLE'- SMOKE BUSH MATURE SIZE: 8-12' HIGH x 8'-12' WIDE




**#12 LOROPETALUM** 'EMERALD SNOW'- FRINGE FLOWER MATURE SIZE: 4' HIGH x 4' WIDE




#2 LAURUS 'SARATOGA'-SARATOGA LAUREL

MATURE SIZE: 12'-30' HIGH x 12'-30' WIDE

**#8 CITRUS 'MEYER DWARF'** MATURE SIZE: 6' HIGH x 6' WIDE



#9 COLEONOMA 'SUNSET GOLD'- BREATH OF HEAVEN MATURE SIZE: 3' HIGH x 3' WIDE



'GREEN BEAUTY'- BOXWOOD MATURE SIZE: 2' HIGH x 2' WIDE (PRUNED)



#17 NEPETA 'SIX HILLS GIANT'- CATMINT MATURE SIZE: 1' HIGH x 3' WIDE




#18 POLYSTICHUM MUNITUM **WESTERN SWORD FERN** MATURE SIZE: 2' HIGH x 2.5' WIDE



#14 WESTRINGIA 'BLUE BOX' - AUSTRALIAN ROSEMARY MATURE SIZE: 4' HIGH x 4' WIDE



#15 LOMONDRA 'LIME TUFF'- GREEN MATT RUSH MATURE SIZE: 2' HIGH x 3' WIDE



MATURE SIZE: 3' HIGH x 3' WIDE





#13 WEIGELA FLORIDA 'VARIEGATA' -WEIGELA

MATURE SIZE: 7' HIGH x 6' WIDE

#1 PISTACHIA 'KEITH DAVIES'- CHINESE PISTACHE

**#7 POLYGALA** 

'PETITE BUTTERFLY'-SWEET PEA SHRUB

MATURE SIZE: 3' HIGH x 3' WIDE

MATURE SIZE: 30'-60' HIGH x 20'-40' WIDE

#19 HYDRANGEA QUERCIFOLIA 'PEE WEE' DWARF OAK LEAF HYDRANGEA MATURE SIZE: 3' HIGH x 3' WIDE




**#20 CHONDROPETALUM ELEPHANTUM CAPE RUSH** MATURE SIZE: 4' HIGH x 5' WIDE




#21 LIGUSTRUM JAPONICUM 'TEXANUM' **GLOSSY PRIVET** MATURE SIZE: 8' HIGH x 5' WIDE



#A ACER PALMATUM -JAPANESE MAPLE (TRANSPLANTED ON SITE) MATURE SIZE: 15'-20' HIGH x 15'-20' WIDE



REVISIONS Copyright 2017 MARA YOUNG LANDSCAPE ARCHITECT All designs drawings, and written materials appearing herein, are protected and constitutionismal and unpublished work of the architect and may not be revised, re-used, copied, or disclosed without the written consent of the Architect. Equipment manufactured by others is excluded. Drawings and specifications are instruments of architectural service, and shall remain the




N

NOL HOM NEW GOLE 622 C

APN# 189-45-035
DRAWN
MY
CHECKED
MY
DATE
6/22/17
SCALE
1/8"=1'-0"
JOB NO.
xxx
SHEET
L-1

SHEETS




	VAL	VE LEGEN	ND	
VALVE #	SYSTEM TYPE	FLOW RATE GPM OR GPH IN	PRECIP. RATE ICHES PER HOUR	
I	DRIP TO FRONT MODERATE (200 LF)	1.02 per 100 LF 2.04 GPH	.64	30-40
2	DRIP TO FRONT MODERATE (100 LF)	1.02 per 100 LF 1.02 GPH	.64	30-40
3	DRIP TO FRONT LOW WATER (200 LF)	1.02 per 100 LF 2.04 GPH	.64	30-40
4	DRIP TO FRONT MODERATE (200 LF)	1.02 per 100 LF 2.04 GPH	.64	30-40
5	SPRAY TO FRONT LAWN	.65 GPM	.5	30
6	SPRAY TO REAR LAWN	.75 GPM	.5	30
7	DRIP TO REAR LOW WATER (175 LF)	1.02 per 100 LF 1.7 GPH	.64	30-40
8	DRIP TO REAR MODERATE (175 LF)	1.02 per 100 LF 1.7 GPH	.64	30-40
9	SPRAY TO REAR LAWN	.75 GPM	.5	30
10	DRIP TO REAR AND SIDE (200 L.F.)	1.02 per 100 LF 2.04 GPH	.64	30-40
П	DRIP TO PATIO EDGE LOW WATER USE (IOOL.F.)	1.02 per 100 LF 1.02 GPH	.64	30-40
12	DRIP TO SIDE YARD LOW WATER USE (200 L.F.)	1.02 per 100 LF 2.04 GPH	.64	30-40

IRRIGATION EQUIPMENT LEGEND				
<u>SYMBOL</u>	DESCRIPTION	<u>NOTES</u>		
0	2-CONTROLLERS IRRITROL SMART DIAL SERIES CONTROLLER 9 STATION WITH WEATHER TRAK SYSTEM FOR ULTIMATE WATER EFFICIENCY	- INSTALL IN LOCTION		
	2- FEBCO ATMOSPERIC BACKFLOW DEVICES			
X	2- NIBCO BRONZE I" GATE VALVES			
•	CONTROL VALVE <u>WEATHERMATIC</u> I" USE PRESSURE REDUCER FOR DRIP IRRIGATION	INSTALL IN 10" CARSON VALVE BOX		
	HUNTER MPIOOO ROTATOR HEADS	REDUCED/MATCHED FLOW SPRAY HEAD		
	MAIN LINE I" SCHEDULE 40 PVC	18" MINIMUM DEPTH USE PRIMER AND GLUE		
	LATERAL LINE SCH. 40 PVC	I" OR AS SHOWN 12" MINIMUM DEPTH		
	NETAFIM TECHLINE 12" SPACING DRIP IRRIGATION SYSTEM	INSTALL AS PER MANUFACTURERS RECOMMENDATIONS		
	SOLID DRIP LINE IN PVC SLEEVE UNDER PAVING	INSTALL AS PER MANUFACTURERS RECOMMENDATIONS		

I HAVE COMPLIED WITH THE CRITERIA OF THE CALIFORNIA WATER EFFICIENT LANDSCAPE ORDINANCE AND APPLIED THEM FOR THE EFFICIENT USE OF WATER IN THE LANDSCAPE AND IRRIGATION DESIGN PLAN.

IRRIGATION SYSTEM PROGRAMMED TO WATER BETWEEN THE HOURS OF 8:00 PM AND 10:00 AM.

IRRIGATION SYSTEM AND COMPONENTS DESIGNED IN SUCH AS WAY AS TO CONSERVE WATER AND PREVENT OVERSPRAY AND RUNOFF



Copyright 2017 MARA YOUNG
LANDSCAPE ARCHITECT
All designs drawings, and written materials appearing herein, are protected and constitutoriginal and unpublished work of the Architect and may not be revised, re-used, copied, or disclosed without the written

REVISIONS

MARA WOUNG
LANDSCAPE ARCHITECT
(650) 327-2644

IRRIGATION PLAN

NEW HOME FOR: GOLDSILVERISLAND 622 COVINGTON WAY LOS ALTOS, CA 94024


ADN# 190 45 03

	APN# 189-45-035	
	DRAWN	
	MY	
	CHECKED	
	MY	
Г	DATE	
	6/28/17	
	SCALE	
	1/8"=1'-0"	
	JOB NO.	
	XXX	
	SHEET	

**L-2** 

OF SHEETS

1 0.5 0.1



REVISIONS Copyright 2017 MARA YOUNG LANDSCAPE ARCHITECT




DIAGRAM HYDROZON

NEW HOME FOR: GOLDSILVERISLA 622 COVINGTON

	APN# 189-45-035	
	DRAWN	-
	MY	
Т	CHECKED	
	MY	
Г	DATE	
	6/21/17	
	SCALE	
	1/8"=1'-0"	
	JOB NO.	
	XXX	
	SHEET	

**L-3** 

1/8"=1'-0"